



FDE36KXZE1

3.6kW

Specifications

Nominal cooling capacity		kW	3.6
Nominal heating capacity		kW	4.0
Power source			1 Phase 220-240V, 50Hz
Power consumption	Cooling	kW	0.05-0.05
	Heating	kW	0.05-0.05
Sound power level		dB(A)	60
Sound pressure level Cooling		dB(A)	P-Hi:46 Hi:38 Me:31 Lo:26
Exterior dimensions unit	H x W x D	mm	210 x 1070 x 690
Net weight		kg	28
Air flow		m ³ /min	P-Hi:13 Hi:10 Me:7 Lo:5.5
Outside air intake			Not possible
Air filter, Q'ty			Pocket Plastic net x2 (Washable)
Remote control(option)			wired:RC-EX3A, RC-E5, RCH-E3 wireless:RCN-E-E3
Installation data Refrigerant piping size		mm(in)	Liquid line:ø6.35(1/4") Gas line:ø12.7(1/2")

The data are measured under the following conditions(ISO-T1).

Cooling: Indoor temp. of 27°CDB, 19°CWB, and outdoor temp. of 35°CDB.

Heating: Indoor temp. of 20°CDB, and outdoor temp. of 7°CDB, 6°CWB.

External static pressure of indoor unit is 10Pa.

The sound level indicates the value of rear-intake type with duct in anechoic chamber. During operation these values are somewhat higher due to ambient conditions.

Schematics

FDE36KXZE1, 45KXZE1, 56KXZE1

